

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 11-048416

(43)Date of publication of application : 23.02.1999

(51)Int.Cl.

B32B 27/20

B32B 27/32

E04F 15/10

(21)Application number : 09-220725

(71)Applicant : TAKIRON CO LTD

(22)Date of filing : 31.07.1997

(72)Inventor : SOU GAKUHO
BUTTA TAKASHI
MORIKAWA TADAYUKI

(54) LENGTHY FLOOR MATERIAL

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a polyolefin lengthy floor material by improving various physical properties such as stain resistance, flaw resistance, recess resistance and flexibility.

SOLUTION: In the lengthy floor material comprising an upper base layer 1 and lower base layer 2, the layer 1 contains 30 to 70 pts.wt. of polyolefin, 69 to 5 pts.wt. of ethylene-vinyl acetate copolymer, 1 to 25 pts.wt. of two-component or three-component copolymer resin containing olefin resin modified by any of methacrylic acid, maleic anhydride and acrylic acid or any of methacrylic acid, maleic anhydride, acrylic acid and acrylic ester and olefin, and 50 to 300 pts.wt. of inorganic filler. And, the layer 2 contains 25 to 70 pts.wt. of polyolefin, 74 to 15 pts.wt. of ethylene-vinylacetate copolymer, 1 to 15 pts.wt. of the modified olefin resin or two-component or three-component copolymer resin, and 50 to 300 pts.wt. of inorganic filler.

